RV BUMPER HITCH (2" X 4" ONLY)

07/13/2020

19101


GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 3,500 LBS. TRAILER WEIGHT & 350 LBS. TONGUE WEIGHT. ***DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.***

WARNING: ALL NON-TRAILER LOADS APPLIED TO THIS PRODUCT MUST BE SUPPORTED BY 18050 STABILIZING STRAPS. ** FAILURE TO PROPERLY SUPPORT NON-TRAILER LOADS WILL VOID PRODUCT WARRANTY** 634

HAVING INSTALLATION QUESTIONS?	CALL TECHNICAL SUPPORT AT 1-877-287-86

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	2	10-10290	BOLT,CAR,1/2-13 UNC,3,GRD8,YZ
2	2	20-00062	NUT, SER-FLANGE,1/2-13 UNC,GRD8,YZ
18	1	19101-PK1U	BOX,RETT,10.125 X 8.625 X 6.0625 (ULINE S-16533)

2



- 1. Locate and mark center of vehicle bumper beam.
- 2. Position hitch over bumper beam on center mark.
- 3. Secure hitch into position using 1/2-13 x 3" carriage bolts and 1/2-13 flange nuts.
- 4. Torque all 1/2" hardware to 110 ft-lbs.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.