



INSTALLATION INSTRUCTIONS

INSTALLATION INSTRUCTIONS

1 • Clean the vehicle before installation of the Hood Protector. Trial fit Hood Protector centrally onto hood. With a non-permanent marker, mark the positions of the, center push on clip, the two fixed clips, and the two push on wing clips.

2 • Press the nut inserts into the five metal clips.

3 • Clean the five noted areas with the alcohol wipe provided. Wipe off any residue with a dry clean cloth. Adhere the abrasive resistant tape strips over the hood lip. Apply tape so approximately half of each strip is adhered to the top side and half is adhered to the underside of hood.

4 • Push the metal wing clips and the centre clip onto hood locating the metal wing clips over the abrasive resistant tape strips on the hood lip, as shown.
IMPORTANT: Ensure that the clips are positioned over abrasive resistant tape and do not come in contact with any of the hood's paint work. Failure to do this may result in permanent paint damage.

5 • Position the fixed clips onto Hood and fit screw plugs through the clips into the holes in hood. Ensure the square boss on screw plugs sit in the square hole in clip. Secure with self tapping screws provided.

6 • Fit the Hood Protector centrally to hood and loosely secure to the centre clip and fixed clips with the small screws and washers provided.

7 • Loosely secure to the wing clips with the small screws and washers provided. Tighten all the screws starting with the centre clip screw then the fixed clip screws then the wing clip screws.
TO REMOVE: Reverse the above procedure.

To Clean: Use mild detergent and water solution (Do NOT use solvents). Avoid the use of automatic "Brush Style" car washes. When closing the hood, do NOT pull on Hood Protector.

- Do not use power tools to install this product.
- No battery operated screw guns.
- The use of power tools during installation may void the product warranty.
- Do not overtighten.

