INSTALLATION INSTRUCTIONS AND PARTS LIST MODEL 583072, 583078, 583088, 584072, 584078, 584088 O-MEGA II 6" OVAL STEPS UNIVERSAL APPLICATION


- 1. READ INSTRUCTIONS COMPLETELY AND CHECK TO MAKE SURE THAT ALL REQUIRED PARTS (LISTED ON THE SERVICE PARTS LIST) ARE ON HAND BEFORE STARTING THE INSTALLATION.
- 2. FOLLOW THE INSTRUCTIONS INCLUDED WITH THE SPECIFIC BRACKET PACKAGE THAT YOU ARE USING, TO MOUNT THE BRACKETS TO YOUR VEHICLE.
- 3. BEFORE ATTACHING THE O-MEGA STEPS TO THE BRACKETS, PLACE THE STEP PADS (ITEM #2) ON TOP OF THE STEP PLATES. USE THE TABLE ON SHEET #2, AS A GUIDE TO POSITION THE STEP PAD FOR YOUR PARTICULAR VEHICLE. WHEN INSTALLING THE PADS ON THE STEPS, DRILL (5) 1/8" HOLE USING THE STEP PAD AS A GUIDE. ATTACH WITH (5) 8-18X1/2" TEK SCREWS (ITEM #6) PROVIDED. REPEAT FOR ALL STEP PADS.
- 4. INSTALL THE REQUIRED NUMBER OF SQUARE HEAD BOLTS INTO THE DESIGNATED SLOTS IN THE BOTTOM OF THE STEP PLATES.
- 5. INSTALL THE END CAPS (ITEM #3) AS SHOWN IN *fig.* 1, TIGHTENING THE NUTS TO 5 LB FT.
- 6. POSITION THE O-MEGA STEP ON THE MOUNTING BRACKETS SO THAT THE SQUARE HEAD SCREWS (ITEM #4) ARE LOCATED IN THE SLOTS OF THE MOUNTING BRACKETS AND THE STEP IS CENTERED, FRONT TO REAR, ON THE VEHICLE. INSTALL 5/16" SERRATED FLANGE NUTS (ITEM #5) ON THE SQUARE HEAD SCREWS (ITEM #4) AND TIGHTEN TO 19 LB FT.

ITEM	PART NO.	QTY	DESCRIPTION	
1	553071	2	EXTRUSION-AL,69.0,OMEGA STP,SILVER	
1	553072	2	EXTRUSION-AL,75.0,OMEGA STP,SILVER	
1	553073	2	EXTRUSION-AL,85.0,OMEGA STP,SILVER	
1	553059	2	EXTRUSION-AL,69.0,OMEGA STP,BLACK	
1	553060	2	EXTRUSION-AL,75.0,0MEGA STP,BLACK	
1	553061	2	EXTRUSION-AL,85.0,OMEGA STP,BLACK	
2	552970	4	ALUM,STP-PAD,BLK,OMEGA-STEP	
3	107956	4	CAP-END,PLSTC,2.95 X 6.70	
4	106880	24	SCREW-SQ HD,5/16-18 X 1,MAGNIGUARD	
5	102680	24	NUT-SERR FLG,HX,SST,WX,5/16-18	
6	107958	20	SCREW-PPH,TEK,#8-18 X 1/2",SST,BZP	

SERVICE PARTS LIST



553116 SHEET 1 OF 2 05OCT16



NOTE: THE ABOVE PAD LOCATIONS ARE ONLY SUGGESTIONS AND MAY BE PLACED AT THE PURCHASERS DISCRESION.



INSTALLATION INSTRUCTIONS AND PARTS LIST MODEL 571054 MEGA STEP BRACKETS: 2010+ TOYOTA 4 RUNNER



PLEASE READ INSTRUCTIONS COMPLETELY BEFORE INSTALLATION.

- 1. LOCATE THE THREE MOUNTING BRACKETS ON THE UNDERSIDE OF THE ROCKER PANEL THAT ARE USED AS SUPPORTS FOR THE ROCKER PANEL MOLDING.
- 2. REMOVE THE TWO M8 BOLTS FROM EACH BRACKET.
- 3. MOUNT THE FRONT BRACKET (ITEM #2), THIS BRACKET WILL MOUNT OVER THE ROCKER PANEL BRACKET, FASTEN WITH THE SUPPLIED M8 BOLTS AND WASHERS (ITEM #4&5). TIGHTEN DOWN TO 19 FT LBS.
- 4. MOUNT THE SECOND AND THIRD BRACKETS (ITEM #3), BY GENTLY PULLING DOWN THE ON THE ROCKER PANEL BRACKET AND SLIDING THE STEP BRACKET (ITEM #3) IN PLACE AND FASTEN WITH THE M8 BOLTS AND WASHERS (ITEM #4&5). TIGHTEN DOWN TO 19 FT LBS.
- 5. PREPARE THE MEGA STEP PLATES FOR MOUNTING BY INSERTING THREE (3) 5/16" SQUARE HEAD SCREWS (ITEM #7) IN THE OUTER SLOT ON THE UNDER SIDE OF EACH STEP.
- 6. POSITION THE MEGA STEP ON THE MOUNTING BRACKETS SO THAT THE SQUARE HEAD SCREWS ARE LOCATED IN THE SLOTS OF THE MOUNTING BRACKETS AND THE STEP IS CENTERED, FRONT TO REAR, ON THE VEHICLE. INSTALL 5/16" SERRATED FLANGE NUTS (ITEM #6) ON THE SQUARE HEAD SCREWS AND TIGHTEN TO 19 FT LBS.



REV A 04JUN13 551808 SHEET 1 OF 3 12APR10

SERVICE PARTS LIST

ITEM	PART NO.	QTY	DESCRIPTION
1	575072	1	MEGA STEP BOARDS 72"
1	585072	1	O-MEGA STEP BOARDS 72"
2	552294	2	STEP BRACKET-FRONT, LH/RH
3	552295	4	STEP BRACKET-REAR, LH/RH
4	102549	12	SCR-HEX,M8X1.25X25MM, ZP
5	100034	12	WSHR-FL,SST, 5/16, ZP
6	102680	12	NUT-SERR FLG,SST,5/16
7	106880	12	SCR-SQ HD,5/16-18X1.00

NOTE: ITEMS #1, 6, &7 ARE PACKAGED WITH THE **BOARDS, AND NOT THE BRACKETS.**



REV A 04JUN13 551808 SHEET 2 OF 3 12APR10

1200 E. Birch St.

