



# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 7/24/2024 Revision date: 7/24/2024 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : Marine & RV Rubbing Compound  
Product code : 620

#### 1.2. Recommended use and restrictions on use

Recommended use : Polishing agent  
Restrictions on use : None known

#### 1.3. Supplier

3D International  
20724 Centre Pointe Pkwy #1  
Santa Clarita, CA 91350  
T 888-999-7627

#### 1.4. Emergency telephone number

Emergency number : (Chemical Spills, Leaks, Fire, Exposure or Accident only)  
CHEMTREC 1-800-424-9300 (in the US & Canada)  
1-703-527-3887 (Outside the US)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Serious eye damage Category 1

Causes serious eye damage

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US)

:



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Causes serious eye damage

Precautionary statements (GHS US)

: Wear eye protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

#### 2.4. Unknown acute toxicity (GHS US)

No additional information available

# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%
Aluminum Oxide	CAS-No.: 1344-28-1	10-30
Undecan-1-ol ethoxylated	CAS-No.: 34398-01-1	<4
White Mineral Oil (Petroleum)	CAS-No.: 8042-47-5	1 – 5

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments : \*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: No first aid should be needed. Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Wash with soap and water. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Immediately rinse with plenty of water (for at least 15 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Causes serious eye damage.
Inhalation	: No adverse effects expected.
Skin	: May cause slight irritation to the skin.
Eyes	: Causes serious eye irritation.
Ingestion	: Irritation to the digestive tract.
Chronic symptoms	: None known.

#### 4.3. Immediate medical attention and special treatment, if necessary

Immediate medical attention is required for eye contact.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use dry chemical, CO2, water spray or regular foam.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: This product is not classified as flammable or combustible.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO2).

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
---------------------------	--

# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ventilate spillage area. Remove ignition sources. Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not touch or walk on the spilled product. Keep unnecessary and unprotected personnel away from the spillage.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For waste disposal after cleaning, see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wear eye protection. Wash thoroughly after handling.

Hygiene measures : Always wash hands after handling the product. Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, cool, well-ventilated area.

Incompatible materials : Store away from strong oxidizers, strong bases, strong acids.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### White Mineral Oil (Petroleum) (8042-47-5)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH OEL TWA	5 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)

# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

### White Mineral Oil (Petroleum) (8042-47-5)

Regulatory reference	ACGIH 2024
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### Aluminum Oxide (1344-28-1)

<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	alpha-Alumina
OSHA PEL (TWA)	15 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: No particular/specific measures required.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

<b>Hand protection:</b>
In case of repeated or prolonged contact wear gloves. Consult glove manufacturer's product information on material suitability and material thickness.
<b>Eye protection:</b>
Chemical goggles
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
Not required for normal conditions of use. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.
<b>Thermal hazard protection:</b>
Not applicable.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: White. Liquid.
Color	: White
Odor	: Characteristic
Odor threshold	: No data available
pH	: 9 – 10
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.

# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.09
Solubility	: Partially soluble. water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 15310 mm²/s @40°C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Undecan-1-ol ethoxylated (34398-01-1)

LD50 dermal rabbit	> 2000 mg/kg Source: Butch Company
--------------------	------------------------------------

#### White Mineral Oil (Petroleum) (8042-47-5)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h No mortality

# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

### Aluminum Oxide (1344-28-1)

LD50 oral rat > 5000 mg/kg

LC50 Inhalation - Rat > 7.6 mg/l 1 h

Skin corrosion/irritation : Not classified  
pH: 9 – 10

### Undecan-1-ol ethoxylated (34398-01-1)

pH 6.5

Serious eye damage/irritation : Causes serious eye damage.  
pH: 9 – 10

### Undecan-1-ol ethoxylated (34398-01-1)

pH 6.5

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified. This product does not contain any component that is considered a carcinogen by IARC, ACGIH, OSHA or NTP.

Reproductive toxicity : Not classified

### Aluminum Oxide (1344-28-1)

NOAEL (animal/male, F0/P) 1000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

### White Mineral Oil (Petroleum) (8042-47-5)

NOAEL (oral,rat,90 days) ≥ 1200 mg/kg body weight

### Aluminum Oxide (1344-28-1)

NOAEC (inhalation,rat,dust/mist/fume,90 days) 0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified

Viscosity, kinematic : 15310 mm²/s @40°C

### White Mineral Oil (Petroleum) (8042-47-5)

Viscosity, kinematic > 3 mm²/s

Hydrocarbon Yes

Symptoms/effects : Causes serious eye damage.

Inhalation : No adverse effects expected.

Skin : May cause slight irritation to the skin.

Eyes : Causes serious eye irritation.

Ingestion : Irritation to the digestive tract.

Chronic symptoms : None known.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### Undecan-1-ol ethoxylated (34398-01-1)

LC50 - Fish [1] 3.9 mg/l Source: ECOTOX

# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

### White Mineral Oil (Petroleum) (8042-47-5)

LC50 - Fish [1] > 100 mg/l

EC50 - Crustacea [1] > 100 mg/l

### Aluminum Oxide (1344-28-1)

EC50 72h - Algae [1] 1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

EC50 72h - Algae [2] 0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

## 12.2. Persistence and degradability

### Marine & RV Rubbing Compound

Persistence and degradability No additional information available.

### Undecan-1-ol ethoxylated (34398-01-1)

Persistence and degradability Readily biodegradable.

### White Mineral Oil (Petroleum) (8042-47-5)

Persistence and degradability Inherently biodegradable.

### Aluminum Oxide (1344-28-1)

Persistence and degradability Biodegradation is not applicable to inorganic compounds.

## 12.3. Bioaccumulative potential

### Undecan-1-ol ethoxylated (34398-01-1)

Partition coefficient n-octanol/water (Log Pow) 4 Source: EPISUITE

## 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.  
Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
Not regulated for transport			

# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

DOT	TDG	IMDG	IATA
<b>14.2. Proper Shipping Name</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

### 14.6. Special precautions for user

**DOT**  
Not regulated

**TDG**  
Not regulated

**IMDG**  
Not regulated

**IATA**  
Not regulated

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Marine & RV Rubbing Compound

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Aluminum Oxide	CAS-No. 1344-28-1	10-30%
----------------	-------------------	--------

### 15.2. International regulations

#### CANADA

#### Undecan-1-ol ethoxylated (34398-01-1)

Listed on the Canadian DSL (Domestic Substances List)



# Marine & RV Rubbing Compound

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

### White Mineral Oil (Petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

### Aluminum Oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

### Marine & RV Rubbing Compound

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

Listed on the Canadian DSL (Domestic Substances List)

### 15.3. US State regulations



#### WARNING:

This product can expose you to Ethylene oxide (Oxirane), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
Aluminum Oxide(1344-28-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Revision date : 7/24/2024

Data sources : This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

#### Indication of changes:

new version.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.