

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015) Issue date: 7/16/2024 Revision date: 7/16/2024 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form Trade name Product code	: Mixture : Marine & RV Poilish : 630
1.2. Recommended use and restrictions	on use
Recommended use Restrictions on use	: Polishing agent : None known
1.3. Supplier	
3D International 20724 Centre Pointe Pkwy #1 Santa Clarita, CA 91350 T 888-999-7627	
1.4. Emergency telephone number	
Emergency number	: (Chemical Spills, Leaks, Fire, Exposure or Accident only) CHEMTREC 1-800-424-9300 (in the US & Canada) 1-703-527-3887 (Outside the US)
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or m	nixture
GHS US classification	nixture
	nixture Causes serious eye damage
GHS US classification	Causes serious eye damage
GHS US classification Serious eye damage Category 1	Causes serious eye damage
GHS US classification Serious eye damage Category 1 2.2. GHS Label elements, including prec GHS US labeling	Causes serious eye damage
GHS US classification Serious eye damage Category 1 2.2. GHS Label elements, including pred GHS US labeling Hazard pictograms (GHS US) Signal word (GHS US) Hazard statements (GHS US)	causes serious eye damage cautionary statements
GHS US classification Serious eye damage Category 1 2.2. GHS Label elements, including prec GHS US labeling Hazard pictograms (GHS US) Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	causes serious eye damage cautionary statements : Causes serious eye damage : Causes serious eye damage : Causes serious eye damage : Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

No additional information available

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Distallates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	15-40
Aluminum Oxide	CAS-No.: 1344-28-1	10-30
White Mineral Oil (Petroleum)	CAS-No.: 8042-47-5	10-30
Undecan-1-ol ethoxylated	CAS-No.: 34398-01-1	1-5
Propylene glycol	CAS-No.: 57-55-6	1-5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments : *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures First-aid measures after inhalation : No first aid should be needed. Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor. First-aid measures after skin contact : Wash with soap and water. Seek medical attention if irritation develops. Take off contaminated clothing. Wash contaminated clothing before reuse. First-aid measures after eye contact Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. First-aid measures after ingestion : Rinse mouth out with water. Call a poison center or a doctor if you feel unwell. 4.2. Most important symptoms and effects (acute and delayed) Symptoms/effects : Causes serious eye damage. Inhalation No adverse effects expected. · Skin : Prolonged or repeated contact may cause skin to become dry. Eyes • Causes serious eye damage. Ingestion Irritation to the digestive tract. · Chronic symptoms None known. :

4.3. Immediate medical attention and special treatment, if necessary

Immediate medical attention is required for eye contact.

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing media		
5 5	 Use dry chemical, CO2, water spray or regular foam. Do not use a solid water stream as it may scatter and spread fire. 	
5.2. Specific hazards arising from the chemical		
Fire hazard	: This product is not classified as flammable or combustible. Could burn but does not ignite readily.	
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO2).	

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing
	apparatus. Complete protective clothing.

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Ventilate spillage area. Remove ignition sources. Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. Remove ignition sources. Avoid contact with skin and eyes. Do not touch or walk on the spilled product. Keep unnecessary and unprotected personnel away from the spillage.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		

6.3. Methods and material for containment and cleaning up For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container. Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For waste disposal after cleaning, see section 13.

SECTION 7: Handling and stor	age
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Avoid contact with eyes, skin and clothing. Wear eye protection. Wash thoroughly after handling. Always wash hands after handling the product. Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, i	ncluding any incompatibilities
Storage conditions Incompatible materials	 Store in dry, cool, well-ventilated area. Store away from strong oxidizers, strong bases, strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

White Mineral Oil (Petroleum) (8042-47-5)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined	
ACGIH OEL TWA	5 mg/m³ (I - Inhalable particulate matter)	
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)	
Regulatory reference	ACGIH 2024	
USA - OSHA - Occupational Exposure Limits		
Local name	Oil mist, mineral	
OSHA PEL (TWA)	5 mg/m³	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Propylene glycol (57-55-6)		
USA - AIHA - Occupational Exposure Limits	-	
WEEL TWA	10 mg/m³	
Aluminum Oxide (1344-28-1)		
USA - OSHA - Occupational Exposure Limits	-	
Local name	alpha-Alumina	
OSHA PEL (TWA)	15 mg/m³	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
8.2. Appropriate engineering controls		
Appropriate engineering controls: No particular/specific measures required.Environmental exposure controls: Avoid release to the environment.		
8.3. Individual protection measures/Personal protective equipment		
Hand protection:		
In case of repeated or prolonged contact wear gloves.	Consult glove manufacturer's product information on material suitability and material thickness.	
Eye protection:		
Wear safety goggles or other eye protection to prevent eye contact.		
Skin and body protection:		
Wear suitable protective clothing		
Respiratory protection:		
Not required for normal conditions of use. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.		

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state Appearance	: Liquid : White, Liauid.	

US - en

Color

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Odor	: Fruity	
Odor threshold	: No data available	
pH	: 10 – 11	
Melting point	: No data available	
Freezing point	: No data available	
Boiling point	: No data available	
Flash point	: > 96 °C Component data	
Relative evaporation rate (butyl acetate=1)	: No data available	
Flammability (solid, gas)	: Not applicable.	
Vapor pressure	: No data available	
Relative vapor density at 20°C	: No data available	
Relative density	: 0.96	
Solubility	: Partially soluble. water.	
Partition coefficient n-octanol/water (Log Pow)	: No data available	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Viscosity, kinematic	: 13900 mm²/s @40°C	
Viscosity, dynamic	: No data available	
Explosion limits	: No data available	
Explosive properties	: None.	
Oxidizing properties	: None.	

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on toxicologica	al effects	
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Undecan-1-ol ethoxylated (34398-01-1)		
LD50 dermal rabbit	> 2000 mg/kg Source: Butch Company	
White Mineral Oil (Petroleum) (8042-47-5)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h No mortality	
Distallates (petroleum), hydrotreated light (64742-47-8)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 Inhalation - Rat	> 6.8 mg/l/4h	
Propylene glycol (57-55-6)		
LD50 oral rat	22000 mg/kg	
LD50 dermal rat	20800 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
Aluminum Oxide (1344-28-1)		
LD50 oral rat	> 5000 mg/kg	
LC50 Inhalation - Rat	> 7.6 mg/l 1 h	
Skin corrosion/irritation :	Not classified pH: 10 – 11	
Undecan-1-ol ethoxylated (34398-01-1)		
рН	6.5	
Serious eye damage/irritation :	Causes serious eye damage. pH: 10 – 11	
Undecan-1-ol ethoxylated (34398-01-1)		
рН	6.5	
Respiratory or skin sensitization:Germ cell mutagenicity:Carcinogenicity:	Not classified Not classified Not classified. This product does not contain any component that is considered a carcinogen by IARC, ACGIH, OSHA or NTP.	
, ,	Not classified	
Distallates (petroleum), hydrotreated light (64		
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male	
Aluminum Oxide (1344-28-1)		
NOAEL (animal/male, F0/P)	1000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	
STOT-single exposure :	Not classified	
STOT-repeated exposure : White Mineral Oil (Petroleum) (8042-47-5)	Not classified	
NOAEL (oral,rat,90 days)	≥ 1200 mg/kg body weight	
	- I zoo mging body woigin	

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Propylene glycol (57-55-6)		
NOAEL (subchronic,oral,animal/male,90 days)	443 mg/kg body weight Animal: cat, Animal sex: male	
Aluminum Oxide (1344-28-1)		
NOAEC (inhalation,rat,dust/mist/fume,90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90- Day Study)	
	Not classified	
Viscosity, kinematic :	13900 mm²/s @40°C	
White Mineral Oil (Petroleum) (8042-47-5)		
Viscosity, kinematic	> 3 mm²/s	
Hydrocarbon	Yes	
Distallates (petroleum), hydrotreated light (64742-47-8)		
Viscosity, kinematic	1.764 mm²/s @40C	
Symptoms/effects :	Causes serious eye damage.	
Inhalation :	No adverse effects expected.	
Skin :	Prolonged or repeated contact may cause skin to become dry.	
Eyes :	Causes serious eye damage.	
Ingestion :	Irritation to the digestive tract.	
Chronic symptoms :	None known.	

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general :	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.	
Undecan-1-ol ethoxylated (34398-01-1)		
LC50 - Fish [1]	3.9 mg/l Source: ECOTOX	
White Mineral Oil (Petroleum) (8042-47-5)		
LC50 - Fish [1]	> 100 mg/l	
EC50 - Crustacea [1]	> 100 mg/l	
Distallates (petroleum), hydrotreated light (64	742-47-8)	
EC50 - Crustacea [1]	> 1000 mg/l	
Propylene glycol (57-55-6)		
LC50 - Fish [1]	51400 mg/l Pimephales promelas (Fathead minnow)	
EC50 - Crustacea [1]	43500 mg/l	
LC50 - Fish [2]	51600 mg/l Oncorhynchus mykiss (Rainbow trout)	
EC50 72h - Algae [1]	19300 mg/l Skeletonema costatum (marine diatom)	
EC50 72h - Algae [2]	24200 mg/l Pseudokirchneriella subcapitata	
EC50 96h - Algae [1]	19100 mg/l Skeletonema costatum (marine diatom)	
EC50 96h - Algae [2]	19000 mg/l Pseudokirchneriella subcapitata	
Aluminum Oxide (1344-28-1)		
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Aluminum Oxide (1344-28-1)		
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
12.2. Persistence and degradability		
Marine & RV Poilish		
Persistence and degradability	No additional information available.	
Undecan-1-ol ethoxylated (34398-01-1)		
Persistence and degradability	Readily biodegradable.	
White Mineral Oil (Petroleum) (8042-47-5)		
Persistence and degradability	Inherently biodegradable.	
Distallates (petroleum), hydrotreated light (64742-47-8)		
Persistence and degradability	Inherently biodegradable.	
Biodegradation	85 % OECD 301F (28d)	
Propylene glycol (57-55-6)		
Persistence and degradability	Readily biodegradable.	
Aluminum Oxide (1344-28-1)		
Persistence and degradability	Biodegradation is not applicable to inorganic compounds.	
12.3. Bioaccumulative potential		
Undecan-1-ol ethoxylated (34398-01-1)		
Partition coefficient n-octanol/water (Log Pow)	4 Source: EPISUITE	
Propylene glycol (57-55-6)		
Partition coefficient n-octanol/water (Log Pow)	-0.92	
Bioaccumulative potential	Low bioaccumulation potential.	
12.4. Mobility in soil		
No additional information available		
12.5. Other adverse effects		

No additional information available

SECTION 13: Disposal considerat	ions
13.1. Disposal methods	
Regional waste regulation Waste treatment methods	Dispose of in accordance with applicable federal, state, and local regulations.Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

DOT	TDG	IMDG	ΙΑΤΑ		
14.1. UN number					
Not regulated for transport					
14.2. Proper Shipping Name					
Not regulated	Not regulated	Not regulated	Not regulated		
14.3. Transport hazard class(es)					
Not regulated	Not regulated	Not regulated	Not regulated		
14.4. Packing group					
Not regulated	Not regulated	Not regulated	Not regulated		
14.5. Environmental hazards					
Not regulated	Not regulated	Not regulated	Not regulated		
No supplementary information available					

14.6. Special precautions for user

DOT Not regulated

riot rogulato

TDG Not regulated

IMDG

Not regulated

IATA Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information		
15.1. US Federal regulations		
Marine & RV Poilish		
SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.	
All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.		
Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		

Aluminum Oxide	CAS-No. 1344-28-1	10-30%

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

15.2. International regulations

CANADA

Undecan-1-ol ethoxylated (34398-01-1)

Listed on the Canadian DSL (Domestic Substances List)

White Mineral Oil (Petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

Distallates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Propylene glycol (57-55-6)

Listed on the Canadian DSL (Domestic Substances List)

Aluminum Oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Marine & RV Poilish

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory Listed on the Canadian DSL (Domestic Substances List)

15.3. US State regulations

This product can expose you to Ethylene oxide (Oxirane), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Propylene glycol(57-55-6)	U.S New Jersey - Right to Know Hazardous Substance List
Aluminum Oxide(1344-28-1)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015) Revision date : 7/16/2024 Data sources : This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

Indication of changes: new version.

Safety Data Sheet (SDS), USA

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.