DIAMOND PROTECH® NANODIAMOND COATING TECHNOLOGY

NANODIAMOND COATING



DIAMOND INTERIOR Plastic/Vinyl/Synthetic Material Protection

Diamond Interior is formulated for interior surfaces such as vinyl, plastic and trim.

Diamond Interior will restore and enrich vehicle interior surfaces while providing up to 12 months of UV, water, and stain resistance.

APPLICATION INSTRUCTIONS

PRECAUTIONS

Apply in temperatures not less than 10C/50F degrees.

Apply when air humidity does not exceed 70%.

If accidentally applied to fabric details, clean up immediately as long exposure of Diamond Interior on fabric can leave grease/oily stain.

APPLICATION TIPS

Diamond Interior is best applied to plastic, vinyl and rubber elements.

Use an additional light source to control your work when polishing treated surfaces.

WHAT YOU'LL NEED

- 2 Microfiber Towels
- Sponge Applicator
- Diamond Body Prep
- Protective Gloves

BEFORE APPLYING - CLEANING AND DECONTAMINATION

Clean all plastic, vinyl and rubber elements of the car with an appropriate degreasing product. Make sure to use products which are wax free and do not form any protective film on the surface treated. Wipe down with Diamond Body Prep and a microfiber towel to remove any residues left from the cleaning product used. Allow the surface to dry completely before application of Diamond Interior.

APPLICATION - APPLICATION TIME: 15 min | 1 LAYER | CURE TIME: 30 min



Shake well for 15 seconds and then apply a small amount (approximate size of 2 Quarters/50 Euro cent coins) of Diamond Interior on a foam applicator.



Using even cross hatch movements, apply Diamond Interior to 1-2 elements at a time. Work horizontally and then cover vertically across the entire surface.



Follow up immediately to polish the treated surfaces with a clean microfiber towel to level and evenly spread the coating, taking care to remove any excess residue in the process. Repeat procedure till all elements are coated.



30 min after application the car is ready for exploitation.