

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SIO2 SPEED SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

SECTION 1. IDENTIFICATION

Product name : CB BLACK PEARL CERAMIC SIO2 SPD 6/16.9OZ

Product code : CBOOBP07

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : PROTECTANT

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Flammable liquid and vapour.

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SIO2 SPEED SPRAY

Version 2.3 Revision Date: 04/10/2024 SDS Number: 600000001598 Date of last issue: 04/09/2024
Date of first issue: 10/30/2018

May be fatal if swallowed and enters airways.
Causes skin irritation.
Harmful if inhaled.
May cause drowsiness or dizziness.

Precautionary statements

Prevention:

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-47-8	>= 50 - < 70
n-Butyl acetate	123-86-4	>= 30 - < 50
Siloxanes and Silicones, 3-[(2-	71750-79-3	>= 5 - < 10

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SIO2 SPEED SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

[aminoethyl)amino]propyl Me, di-Me

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- | | |
|---|---|
| General advice | : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended. |
| If inhaled | : Move to fresh air.
IF INHALED: Call a POISON CENTER/ doctor if you feel unwell.
If unconscious, place in recovery position and seek medical advice.
Keep patient warm and at rest.
If symptoms persist, call a physician. |
| In case of skin contact | : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician. |
| In case of eye contact | : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing. |
| If swallowed | : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : May be fatal if swallowed and enters airways.
Causes skin irritation.
Harmful if inhaled.
May cause drowsiness or dizziness. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---------------------------------------|---|
| Suitable extinguishing media | : Water spray
Carbon dioxide (CO2)
Dry chemical
Alcohol-resistant foam |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |

**Car Brite™ CB BLACK PEARL CERAMIC SiO₂
SPEED SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

- Hazardous combustion products : Carbon oxides
Silicon oxides
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Do not use a solid water stream as it may scatter and spread fire.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SIO2 SPEED SPRAY

Version 2.3 Revision Date: 04/10/2024 SDS Number: 600000001598 Date of last issue: 04/09/2024
Date of first issue: 10/30/2018

ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
n-Butyl acetate	123-86-4	TWA	150 ppm 710 mg/m3	NIOSH REL
		ST	200 ppm 950 mg/m3	NIOSH REL
		TWA	150 ppm 710 mg/m3	OSHA Z-1
		TWA	150 ppm 710 mg/m3	OSHA P0
		STEL	200 ppm 950 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SIO2 SPEED SPRAY

Version 2.3 Revision Date: 04/10/2024 SDS Number: 600000001598 Date of last issue: 04/09/2024
Date of first issue: 10/30/2018

Hazardous components without workplace control parameters

Components	CAS-No.
Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me	71750-79-3

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : transparent

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SiO₂ SPEED SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

Flash point	:	55 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	0.88 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	practically insoluble
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides Silicon oxides

**Car Brite™ CB BLACK PEARL CERAMIC SiO₂
SPEED SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Remarks: Breathing air containing n-butyl acetate, which results from its use in aerosol applications, may cause delayed lung injury. Acute toxicity estimate: 2.1 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method

Components:**Distillates (petroleum):**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, male and female): Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: No adverse effect has been observed in acute dermal toxicity tests.

n-Butyl acetate:

Acute oral toxicity	:	LD50 (Rat, female): 10.8 g/kg Method: OECD Test Guideline 423
Acute inhalation toxicity	:	LC50 (Rat): > 21 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Acute dermal toxicity	:	LD50 (Rabbit): > 14,112 mg/kg Method: OECD Test Guideline 402

**Car Brite™ CB BLACK PEARL CERAMIC SIO2
SPEED SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me:

Acute oral toxicity : LD50 (Rat): > 2,010 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.105 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist**Skin corrosion/irritation**

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:**Distillates (petroleum):**

Result: Irritating to skin.

n-Butyl acetate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me:

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**Distillates (petroleum):**

Result: Possibly irritating to eyes

n-Butyl acetate:

Species: Rabbit

Result: Possibly irritating to eyes

Method: OECD Test Guideline 405

Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me:

Result: Irritating to eyes.

**Car Brite™ CB BLACK PEARL CERAMIC SIO2
SPEED SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:**n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Cell type: Bone marrow
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:**Distillates (petroleum):**

Assessment: May cause drowsiness or dizziness.

n-Butyl acetate:

Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SIO2 SPEED SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No.	: UN 1993
Proper shipping name	: Flammable liquid, n.o.s. (Butyl acetate, Hydrotreated Petroleum Distillates)
Class	: 3
Packing group	: III

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SIO2 SPEED SPRAY

Version 2.3 Revision Date: 04/10/2024 SDS Number: 600000001598 Date of last issue: 04/09/2024
Date of first issue: 10/30/2018

Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Butyl acetate, Hydrotreated Petroleum Distillates)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(Butyl acetate, Hydrotreated Petroleum Distillates)
Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
n-Butyl acetate	123-86-4	5000	*
Methanol	67-56-1	100	100 (F003)*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Acute toxicity (any route of exposure)

SAFETY DATA SHEET



Car Brite™ CB BLACK PEARL CERAMIC SiO2 SPEED SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001598	Date of first issue: 10/30/2018

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 04/10/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN