

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Solvent

Version 5.3 Revision Date: 04/10/2024 SDS Number: 600000000772 Date of last issue: 04/09/2024
Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : CB ERADICATOR 4/1 GA

Product code : CBOOF006-03

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Auditory system)

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Sol-vent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Sol-vent

Version 5.3 Revision Date: 04/10/2024 SDS Number: 600000000772 Date of last issue: 04/09/2024
Date of first issue: 05/23/2016

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum)	64742-49-0	$\geq 50 - < 70$
Distillates (petroleum)	64742-47-8	$\geq 20 - < 30$
Xylene	1330-20-7	$\geq 10 - < 20$
n-Butyl acetate	123-86-4	$\geq 5 - < 10$
n-Heptane	142-82-5	$\geq 5 - < 10$
Octane	111-65-9	$\geq 5 - < 10$
Ethylbenzene	100-41-4	$\geq 5 - < 10$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
Causes skin irritation.

Car Brite™ ERADICATOR™ Body Prep Sol-vent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Do not use a solid water stream as it may scatter and spread fire.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

SAFETY DATA SHEET


Car Brite™ ERADICATOR™ Body Prep Sol-vent

 Version
5.3

 Revision Date:
04/10/2024

 SDS Number:
600000000772

 Date of last issue: 04/09/2024
Date of first issue: 05/23/2016

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum)	64742-49-0	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0
n-Butyl acetate	123-86-4	TWA	150 ppm 710 mg/m ³	NIOSH REL
		ST	200 ppm 950 mg/m ³	NIOSH REL
		TWA	150 ppm 710 mg/m ³	OSHA Z-1
		TWA	150 ppm 710 mg/m ³	OSHA P0
		STEL	200 ppm 950 mg/m ³	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
n-Heptane	142-82-5	TWA	85 ppm 350 mg/m ³	NIOSH REL
		C	440 ppm 1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
		STEL	500 ppm 2,000 mg/m ³	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Octane	111-65-9	TWA	75 ppm 350 mg/m ³	NIOSH REL
		C	385 ppm 1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,350 mg/m ³	OSHA Z-1
		TWA	300 ppm 1,450 mg/m ³	OSHA P0
		STEL	375 ppm 1,800 mg/m ³	OSHA P0
		TWA	300 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	NIOSH REL

SAFETY DATA SHEET


Car Brite™ ERADICATOR™ Body Prep Sol-vent

Version 5.3 Revision Date: 04/10/2024 SDS Number: 600000000772 Date of last issue: 04/09/2024
 Date of first issue: 05/23/2016

		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
Distillates (petroleum)	64742-47-8

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Xylene	1330-20-7	Methylhip-puric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g cre-atinine	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-oxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate:

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Impervious clothing
Flame-resistant clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: orange
Odour	: No data available
Odour Threshold	: not determined
pH	: No data available
Melting point/freezing point	: -26 °C
Boiling point/boiling range	: > 150 °F (1013.25 hPa)
Flash point	: 12 °C Method: Pensky-Martens closed cup
Flammability (solid, gas)	: No data available
Flammability (liquids)	: Static-accumulating flammable liquid.
Self-ignition	: 232 °C
Upper explosion limit / Upper flammability limit	: 8 %(V) The value is calculated
Lower explosion limit / Lower flammability limit	: 1 %(V) The value is calculated
Vapour pressure	: 16 hPa (20 °C) The value is calculated
Density	: 0.777 g/cm3
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: not determined

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : 47.6 mm²/s (40 °C)
Oxidizing properties : No data available
Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.
Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Acids
Bases
Amines
Nitrous acid and other nitrosating agents
Combustible material
Strong oxidizing agents
Strong reducing agents
Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method
Acute inhalation toxicity : Remarks: Breathing air containing n-butyl acetate, which results from its use in aerosol applications, may cause delayed lung injury.
Acute toxicity estimate: 50.57 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Car Brite™ ERADICATOR™ Body Prep Sol-vent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Distillates (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6700 ppm
Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat, female): 10.8 g/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 14,112 mg/kg
Method: OECD Test Guideline 402

n-Heptane:

Acute oral toxicity : LD50 (Rat): Expected > 5,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat, male and female): > 29.29 mg/l
Exposure time: 4 h

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): Expected > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.
Remarks: Information given is based on data obtained from similar substances.

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): ca. 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 17,800 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Naphtha (petroleum):

Result: Irritating to skin.

Distillates (petroleum):

Result: Irritating to skin.

Xylene:

Assessment: Irritating to skin.
Result: Irritating to skin.

n-Butyl acetate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

n-Heptane:

Result: Irritating to skin.

Octane:

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Result: Irritating to skin.

Ethylbenzene:

Result: Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Distillates (petroleum):

Result: Possibly irritating to eyes

Xylene:

Result: Irritating to eyes.

n-Butyl acetate:

Species: Rabbit

Result: Possibly irritating to eyes

Method: OECD Test Guideline 405

n-Heptane:

Result: Possibly irritating to eyes

Ethylbenzene:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

n-Heptane:

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

Germ cell mutagenicity

Not classified based on available information.

Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Components:**n-Butyl acetate:**

Genotoxicity in vitro	:	Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay) Result: negative
Genotoxicity in vivo	:	Test Type: Micronucleus test Species: Mouse Cell type: Bone marrow Method: OECD Test Guideline 474 Result: negative

n-Heptane:

Genotoxicity in vitro	:	Remarks: In vitro tests did not show mutagenic effects
-----------------------	---	--

Carcinogenicity

Not classified based on available information.

Components:**Ethylbenzene:**

Carcinogenicity - Assessment	:	Not classifiable as a human carcinogen.
------------------------------	---	---

IARC

Group 2B: Possibly carcinogenic to humans

Ethylbenzene	100-41-4
--------------	----------

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:**Naphtha (petroleum):**

Reproductive toxicity - Assessment	:	Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.
------------------------------------	---	--

STOT - single exposure

May cause drowsiness or dizziness.

Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

Components:**Naphtha (petroleum):**

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

Distillates (petroleum):

Assessment: May cause drowsiness or dizziness.

Xylene:

Assessment: May cause drowsiness or dizziness., May cause respiratory irritation.

n-Butyl acetate:

Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

n-Heptane:

Assessment: May cause drowsiness or dizziness.

Octane:

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:**Ethylbenzene:**

Target Organs: Auditory system
Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:**Naphtha (petroleum):**

May be fatal if swallowed and enters airways.

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Xylene:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

n-Heptane:

May be fatal if swallowed and enters airways.

Octane:

May be fatal if swallowed and enters airways.

Ethylbenzene:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Petroleum Naphtha, Xylene)
Class : 3
Packing group : II
Labels : 3

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Sol-vent

Version 5.3 Revision Date: 04/10/2024 SDS Number: 600000000772 Date of last issue: 04/09/2024
Date of first issue: 05/23/2016

Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Petroleum Naphtha, Xylene)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(Petroleum Naphtha, Xylene)
Class : 3
Packing group : II
Labels : 3
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	599
Xylene	1330-20-7	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)
Reproductive toxicity

SAFETY DATA SHEET



Car Brite™ ERADICATOR™ Body Prep Solvent

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.3	04/10/2024	600000000772	Date of first issue: 05/23/2016

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

Xylene	1330-20-7	>= 10 - < 20 %
Ethylbenzene	100-41-4	>= 5 - < 10 %


California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, Benzene, Naphthalene, C.I. Solvent Yellow 14, Aniline, Nitrobenzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, Nitrobenzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 04/10/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN