

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

---

### SECTION 1. IDENTIFICATION

Product name : CB LACQUER THINNER PL 5 GA

Product code : 777707

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use : SOLVENT

Restrictions on use : Use only outdoors or in a well-ventilated area.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 1 (Central nervous system, Eyes)

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue:
2.3	04/10/2024	600000001596	04/09/2024
			Date of first issue: 10/17/2018

Specific target organ toxicity : Category 2 (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision))  
- repeated exposure (Inhalation)

Aspiration hazard : Category 1

### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.  
Toxic if swallowed, in contact with skin or if inhaled.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause genetic defects.  
Suspected of causing cancer.  
Suspected of damaging the unborn child.  
Causes damage to organs (Central nervous system, Eyes).  
May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
Rinse mouth.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.  
IF IN EYES: Rinse cautiously with water for several minutes.

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed: Call a POISON CENTER or doctor/ physician.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.  
If eye irritation persists: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Methanol	67-56-1	$\geq 30 - \leq 50$
Toluene	108-88-3	$\geq 30 - \leq 50$
Naphtha (petroleum)	64742-49-0	$\geq 0 - \leq 20$
Naphtha (petroleum)	64742-89-8	$\geq 0 - \leq 20$
Petroleum distillates	68410-97-9	$\geq 0 - \leq 20$
Acetone	67-64-1	$\geq 10 - \leq 20$
n-Heptane	142-82-5	$\geq 0.1 - \leq 1$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

In case of skin contact : If on clothes, remove clothes.  
Call a physician or poison control centre immediately.

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

- Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Get medical attention immediately.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Toxic if swallowed, in contact with skin or if inhaled.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause genetic defects.  
Suspected of causing cancer.  
Suspected of damaging the unborn child.  
Causes damage to organs.  
May cause damage to organs through prolonged or repeated exposure if inhaled.  
This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.  
This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Ensure adequate ventilation.  
Avoid breathing dust.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Evacuate personnel to safe areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.  
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.

# SAFETY DATA SHEET



## LACQUER THINNER

Version  
2.3

Revision Date:  
04/10/2024

SDS Number:  
600000001596

Date of last issue: 04/09/2024  
Date of first issue: 10/17/2018

Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm 260 mg/m3	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0

## SAFETY DATA SHEET



## LACQUER THINNER

Version  
2.3Revision Date:  
04/10/2024SDS Number:  
600000001596Date of last issue: 04/09/2024  
Date of first issue: 10/17/2018

Naphtha (petroleum)	64742-49-0	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Naphtha (petroleum)	64742-89-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Petroleum distillates	68410-97-9	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
n-Heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

## Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after	0.03 mg/l	ACGIH BEI

# SAFETY DATA SHEET



## LACQUER THINNER

Version 2.3      Revision Date: 04/10/2024      SDS Number: 600000001596      Date of last issue: 04/09/2024  
Date of first issue: 10/17/2018

				exposure ceases)		
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear as appropriate:  
Impervious clothing  
Flame-resistant clothing  
Safety shoes  
Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
Avoid contact with skin, eyes and clothing.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat or drink.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid



# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

---

Colour	:	colourless
Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	56 - 150 °C
Flash point	:	-20 °C Value for Component
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	7 - 36.5 %(V) No data available
Lower explosion limit / Lower flammability limit	:	0.8 - 6 %(V) No data available
Vapour pressure	:	231 mmHg (25 °C) The value is calculated
Relative vapour density	:	No data available
Density	:	0.808 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Molecular weight	:	No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

---

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids  
Amines  
Aluminium  
halogens  
Lead  
Peroxides  
Reducing agents  
Strong oxidizing agents  
Strong bases  
Zinc  
Alkalis  
Ammonia  
Metal salts

Hazardous decomposition products : Carbon oxides

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Eye contact  
Skin contact  
Ingestion

#### Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled.

#### Product:

Acute oral toxicity : Acute toxicity estimate: 249.99 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 6.8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 635.58 mg/kg  
Method: Calculation method

#### Components:

##### **Methanol:**

Acute oral toxicity : LDLo (Humans): 300 mg/kg  
Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: dust/mist  
Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg  
Assessment: The component/mixture is toxic after single con-

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

---

tact with skin.

### **Toluene:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, males): 25.7 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): 12,124 mg/kg

### **Naphtha (petroleum):**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402

### **Naphtha (petroleum):**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402

### **Petroleum distillates:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg

### **Acetone:**

Acute oral toxicity	:	LD50 (Rat, female): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, female): 76 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): > 7,426 mg/kg

### **n-Heptane:**

Acute oral toxicity	:	LD50 (Rat): Expected > 5,000 mg/kg Remarks: Information given is based on data obtained from similar substances.
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 29.29 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Acute dermal toxicity	:	LD50 (Rabbit): Expected > 2,000 mg/kg

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

---

Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Remarks: Information given is based on data obtained from similar substances.

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Product:**

Remarks: May cause skin irritation and/or dermatitis.

#### **Components:**

##### **Methanol:**

Species: Rabbit

Result: No skin irritation

##### **Toluene:**

Result: Irritating to skin.

##### **Naphtha (petroleum):**

Species: Rabbit

Result: Irritating to skin.

##### **Naphtha (petroleum):**

Species: Rabbit

Result: Irritating to skin.

##### **Petroleum distillates:**

Species: Rabbit

Result: Irritating to skin.

##### **Acetone:**

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

##### **n-Heptane:**

Result: Irritating to skin.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

#### **Components:**

##### **Methanol:**

Species: Rabbit

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

---

Result: Possibly irritating to eyes

### **Toluene:**

Result: Irritating to eyes.

### **Naphtha (petroleum):**

Species: Rabbit

Result: Irritating to eyes.

### **Naphtha (petroleum):**

Species: Rabbit

Result: Irritating to eyes.

### **Petroleum distillates:**

Species: Rabbit

Result: Irritating to eyes.

### **Acetone:**

Result: Irritating to eyes.

Assessment: Irritating to eyes.

### **n-Heptane:**

Result: Possibly irritating to eyes

## **Respiratory or skin sensitisation**

### **Skin sensitisation**

Not classified based on available information.

### **Respiratory sensitisation**

Not classified based on available information.

### **Components:**

#### **Methanol:**

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

#### **Toluene:**

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Not a skin sensitizer.

#### **Naphtha (petroleum):**

Test Type: Buehler Test

Species: Guinea pig

Result: Not a skin sensitizer.

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

---

### **Naphtha (petroleum):**

Test Type: Buehler Test  
Species: Guinea pig  
Result: Not a skin sensitizer.

### **n-Heptane:**

Test Type: Maximisation Test  
Species: Guinea pig  
Result: Did not cause sensitisation on laboratory animals.  
Remarks: Information given is based on data obtained from similar substances.

### **Germ cell mutagenicity**

May cause genetic defects.

### **Components:**

#### **Petroleum distillates:**

Germ cell mutagenicity - Assessment : Positive result(s) from in vivo heritable germ cell mutagenicity tests in mammals

#### **n-Heptane:**

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

### **Carcinogenicity**

Suspected of causing cancer.

### **Components:**

#### **Naphtha (petroleum):**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

#### **Naphtha (petroleum):**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

#### **Petroleum distillates:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

### **IARC**

Group 2B: Possibly carcinogenic to humans

Petroleum distillates 68410-97-9

### **OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### **NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

**Reproductive toxicity**

Suspected of damaging the unborn child.

**Components:****Toluene:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**Naphtha (petroleum):**

Reproductive toxicity - Assessment : Fertility classification not possible from current data.  
Embryotoxicity classification not possible from current data.

**Naphtha (petroleum):**

Reproductive toxicity - Assessment : Fertility classification not possible from current data.  
Embryotoxicity classification not possible from current data.

**STOT - single exposure**

May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system, Eyes).

**Components:****Methanol:**

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

**Toluene:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

**Naphtha (petroleum):**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

**Naphtha (petroleum):**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

**Petroleum distillates:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

**Acetone:**

Exposure routes: Inhalation

Target Organs: Nervous system

# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

---

Assessment: May cause drowsiness or dizziness.

### **n-Heptane:**

Assessment: May cause drowsiness or dizziness.

### **STOT - repeated exposure**

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

### **Components:**

#### **Toluene:**

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Components:**

#### **Toluene:**

May be fatal if swallowed and enters airways.

### **Naphtha (petroleum):**

May be fatal if swallowed and enters airways.

### **Naphtha (petroleum):**

May be fatal if swallowed and enters airways.

### **Petroleum distillates:**

May be fatal if swallowed and enters airways.

### **Acetone:**

May be harmful if swallowed and enters airways.

### **n-Heptane:**

May be fatal if swallowed and enters airways.

### **Further information**

### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Toxicity**

Additional ecological : An environmental hazard cannot be excluded in the event of



# SAFETY DATA SHEET



## LACQUER THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
2.3	04/10/2024	600000001596	Date of first issue: 10/17/2018

information

unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

##### IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	Paint related material
Class	:	3
Packing group	:	II
Labels	:	3
Packing instruction (cargo aircraft)	:	364
Packing instruction (passenger aircraft)	:	353

##### IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL ( )
Class	:	3
Packing group	:	II
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
Marine pollutant	:	yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

UN/ID/NA number	:	UN 1263
Proper shipping name	:	Paint related material
Class	:	3
Packing group	:	II

# SAFETY DATA SHEET



## LACQUER THINNER

Version 2.3      Revision Date: 04/10/2024      SDS Number: 600000001596      Date of last issue: 04/09/2024  
Date of first issue: 10/17/2018

Labels : 3  
ERG Code : 128  
Marine pollutant : no

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1000	2856
Methanol	67-56-1	100	100 (F003)
Acetone	67-64-1	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Xylene	1330-20-7	100	100 (F003)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

##### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Acute toxicity (any route of exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Germ cell mutagenicity  
Carcinogenicity

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Methanol	67-56-1	>= 30 - < 50 %
Toluene	108-88-3	>= 30 - < 50 %

##### California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, Ethylbenzene, Naphthalene, Cumene, which is/are known to the State of California to cause cancer, and Methanol, Toluene, Benzene, n-Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# SAFETY DATA SHEET



## LACQUER THINNER

Version  
2.3

Revision Date:  
04/10/2024


SDS Number:  
600000001596

Date of last issue: 04/09/2024  
Date of first issue: 10/17/2018

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA:



Revision Date : 04/10/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN