

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

### SECTION 1. IDENTIFICATION

Product name : CB SLEEK WAX 4/1 GA

Product code : CBOOA039-03

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use : WAX

Restrictions on use : Use only outdoors or in a well-ventilated area.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

#### GHS label elements

Hazard pictograms :



Signal word : Warning

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

---

Hazard statements : Flammable liquid and vapour.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/ attention.  
If skin irritation or rash occurs: Get medical advice/ attention.  
If eye irritation persists: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version 3.4      Revision Date: 04/10/2024      SDS Number: 600000000702      Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum)	64742-49-0	$\geq 10 - < 20$
Distillates (petroleum)	64742-47-8	$\geq 5 - < 10$
White mineral oil	8042-47-5	$\geq 1 - < 5$
Silica Amorphous	7631-86-9	$\geq 1 - < 5$
Morpholine	110-91-8	$\geq 1 - < 3$
n-Heptane	142-82-5	$\geq 1 - < 5$
Octane	111-65-9	$\geq 1 - < 5$
Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine	4719-04-4	$\geq 0.1 - < 1$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

Suspected of damaging fertility or the unborn child.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides  
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Avoid breathing dust.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Evacuate personnel to safe areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version 3.4      Revision Date: 04/10/2024      SDS Number: 600000000702      Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.  
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.  
Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum)	64742-49-0	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Distillates (petroleum)	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3	ACGIH

## SAFETY DATA SHEET


**Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover**

 Version  
3.4

 Revision Date:  
04/10/2024

 SDS Number:  
600000000702

 Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

			(total hydrocarbon vapor)	
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
White mineral oil	8042-47-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Silica Amorphous	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL
Morpholine	110-91-8	TWA	20 ppm	ACGIH
		TWA	20 ppm 70 mg/m3	NIOSH REL
		ST	30 ppm 105 mg/m3	NIOSH REL
		TWA	20 ppm 70 mg/m3	OSHA Z-1
		TWA	20 ppm 70 mg/m3	OSHA P0
		STEL	30 ppm 105 mg/m3	OSHA P0
n-Heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Octane	111-65-9	TWA	75 ppm 350 mg/m3	NIOSH REL
		C	385 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,350 mg/m3	OSHA Z-1
		TWA	300 ppm 1,450 mg/m3	OSHA P0
		STEL	375 ppm 1,800 mg/m3	OSHA P0

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version 3.4      Revision Date: 04/10/2024      SDS Number: 600000000702      Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

		TWA	300 ppm	ACGIH
--	--	-----	---------	-------

### Hazardous components without workplace control parameters

Components	CAS-No.
Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine	4719-04-4

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter.

**Hand protection**

**Remarks** : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

**Eye protection** : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

**Skin and body protection** : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear as appropriate:  
Impervious clothing  
Flame-resistant clothing  
Safety shoes

**Hygiene measures** : Handle in accordance with good industrial hygiene and safety practice.  
When using do not smoke.  
When using do not eat or drink.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid

**Colour** : black

**Odour** : solvent-like

**Odour Threshold** : No data available

**pH** : No data available

**Melting point/freezing point** : No data available

**Boiling point/boiling range** : > 150 °F  
(1013.25 hPa)

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

Flash point	:	51.1 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	ca. 0.954 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	2357 mm <sup>2</sup> /s (40 °C)
Oxidizing properties	:	No data available
Molecular weight	:	Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids acrylates Alcohols Aldehydes



# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

Bases  
halogens  
glycols  
Halogenated compounds  
Iron  
isocyanates  
Ketones  
Metals  
Nitrous acid and other nitrosating agents  
organic anhydrides  
Reducing agents  
Strong oxidizing agents

Hazardous decomposition products : Carbon oxides  
Silicon oxides

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Eye contact  
Ingestion

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: 30.41 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

#### Components:

##### White mineral oil:

Acute oral toxicity	: LD50 (Rat): 50,000 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Assessment: No adverse effect has been observed in acute dermal toxicity tests.

##### Silica Amorphous:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 (Rat): > 2.08 mg/l

**Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

---

Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

**Morpholine:**

Acute oral toxicity : LD50 (Rat): ca. 1,900 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): ca. 500 mg/kg

**n-Heptane:**

Acute oral toxicity : LD50 (Rat): Expected > 5,000 mg/kg  
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat, male and female): > 29.29 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): Expected > 2,000 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.  
Remarks: Information given is based on data obtained from similar substances.

**Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Acute oral toxicity : LD50 (Rat, male and female): 1,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0.371 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 4,000 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Result: Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

---

Remarks: May cause skin irritation and/or dermatitis.

### **Components:**

#### **Naphtha (petroleum):**

Result: Irritating to skin.

#### **Distillates (petroleum):**

Result: Repeated exposure may cause skin dryness or cracking.

#### **White mineral oil:**

Assessment: No skin irritation

Result: No skin irritation

#### **Silica Amorphous:**

Result: Possibly irritating to skin

#### **Morpholine:**

Result: Corrosive after 3 minutes or less of exposure

#### **n-Heptane:**

Result: Irritating to skin.

#### **Octane:**

Result: Irritating to skin.

#### **Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Method: OECD Test Guideline 404

Result: No skin irritation

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

### **Components:**

#### **White mineral oil:**

Result: No eye irritation

Assessment: No eye irritation

#### **Silica Amorphous:**

Result: Possibly irritating to eyes

**Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

---

**Morpholine:**

Result: Irreversible effects on the eye

**n-Heptane:**

Result: Possibly irritating to eyes

**Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Result: Irritating to eyes.

Method: OECD Test Guideline 405

**Respiratory or skin sensitisation****Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Product:**

Remarks: May cause allergic skin reaction.

**Components:****n-Heptane:**

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

**Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Species: Guinea pig

Result: May cause sensitisation by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Morpholine:**

Genotoxicity in vitro

: Test Type: unscheduled DNA synthesis assay  
Test system: rat hepatocytes  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 482  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Test system: mouse lymphoma cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: positive

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

---

### n-Heptane:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

### Carcinogenicity

Not classified based on available information.

#### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

### Components:

#### Naphtha (petroleum):

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

### STOT - single exposure

May cause drowsiness or dizziness.

### Components:

#### Naphtha (petroleum):

Exposure routes: Inhalation  
Target Organs: Central nervous system  
Assessment: May cause drowsiness or dizziness.

#### Distillates (petroleum):

Target Organs: Central nervous system  
Assessment: May cause drowsiness or dizziness.

### n-Heptane:

Assessment: May cause drowsiness or dizziness.

### Octane:

Exposure routes: Inhalation  
Target Organs: Central nervous system  
Assessment: May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

### **Components:**

#### **Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: Causes damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

Not classified based on available information.

### **Product:**

No aspiration toxicity classification

### **Components:**

#### **Naphtha (petroleum):**

May be fatal if swallowed and enters airways.

#### **Distillates (petroleum):**

May be fatal if swallowed and enters airways.

#### **n-Heptane:**

May be fatal if swallowed and enters airways.

#### **Octane:**

May be fatal if swallowed and enters airways.

### **Further information**

### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## SECTION 12. ECOLOGICAL INFORMATION

### **Toxicity**

Additional ecological information	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.
-----------------------------------	---	---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents.

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
3.4	04/10/2024	600000000702	Date of first issue: 05/23/2016

Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

##### IATA-DGR

UN/ID No.	: UN 1993
Proper shipping name	: Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA)
Class	: 3
Packing group	: III
Labels	: 3
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

##### IMDG-Code

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM NAPHTHA)
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
Marine pollutant	: no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

UN/ID/NA number	: UN 1993
Proper shipping name	: Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM NAPHTHA)
Class	: 3
Packing group	: III
Labels	: 3
ERG Code	: 128
Marine pollutant	: no

### SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version 3.4      Revision Date: 04/10/2024      SDS Number: 600000000702      Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethylbenzene	100-41-4	100	100 (F003)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)
Benzene	71-43-2	10	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitisation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### California Prop. 65

WARNING: This product can expose you to chemicals including Carbon Black, Ethylbenzene, Benzene, Naphthalene, Silica, crystalline (Quartz), Diethanolamine, which is/are known to the State of California to cause cancer, and Toluene, Benzene, Ethylene glycol monomethyl ether, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



# SAFETY DATA SHEET



## Car Brite™ SLEEK™ Dark Paint - Oxidation & Swirl Mark Remover

Version  
3.4

Revision Date:  
04/10/2024


SDS Number:  
600000000702

Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

### SECTION 16. OTHER INFORMATION

#### Further information

#### NFPA:



Revision Date : 04/10/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN