

SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000130 Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : CB SELECT S-FREE ALL PURP DRSG 5 GA

Product code : 702261

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num-

ber

1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : TIRE SHINE / DRESSING

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4

Specific target organ toxicity :

- single exposure

Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms





Signal word : Danger

Hazard statements : Combustible liquid.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000130 Date of first issue: 05/23/2016

Precautionary statements : Prevention:

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel un-

well.

Do NOT induce vomiting.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-47-8	>= 70 - < 90

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000130 Date of first issue: 05/23/2016

In case of skin contact : If on clothes, remove clothes.

If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed : Obtain medical attention.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air

and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the

point of release.

Hazardous combustion prod-

ucts

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use a water spray to cool fully closed containers.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment. Remove all sources of ignition.

Ensure adequate ventilation.

Avoid breathing dust.

Persons not wearing protective equipment should be excluded



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version **Revision Date:** Date of last issue: 04/10/2024 SDS Number: 600000000130 3.4 04/23/2025 Date of first issue: 05/23/2016

from area of spill until clean-up has been completed.

Environmental precautions Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for nonconductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protec-

tion Association document NFPA 77.

Keep away from open flames, hot surfaces and sources of

ianition.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of ters / Permissible		
		exposure)	concentration	



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version **Revision Date:** SDS Number: Date of last issue: 04/10/2024 60000000130 3.4 04/23/2025 Date of first issue: 05/23/2016

Distillates (petroleum)	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3	ACGIH
			(total hydrocarbon	
			vapor)	
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures Provide sufficient mechanical (general and/or local exhaust)

> ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection In the case of vapour formation use a respirator with an ap-

proved filter.

Hand protection

Wear resistant gloves (consult your safety equipment suppli-Remarks

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Not required under normal conditions of use. Wear splash-Eye protection

proof safety goggles if material could be misted or splashed

into eyes.

Choose body protection according to the amount and con-Skin and body protection

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing

Safety shoes

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not smoke. When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Colour blue green

Odour fruity

Odour Threshold not determined



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 60000000130 Date of first issue: 05/23/2016

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 80 °C

The value is calculated

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Static-accumulating flammable liquid.

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Density : 0.835 g/cm3 (20 °C)

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : not determined

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000130 Date of first issue: 05/23/2016

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Strong reducing agents

Hazardous decomposition

products

Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

Skin contact

Eye contact

Ingestion

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum):

Result: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000130 Date of first issue: 05/23/2016

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Distillates (petroleum):

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vom-

iting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 60000000130 Date of first issue: 05/23/2016

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Ethyl acetate	141-78-6	100	100 (F003)
Diethyl phthalate	84-66-2	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Hazard not otherwise classified (physical hazards)

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard



SELECT SILICONE-FREE ALL PURPOSE DRSG VOC COMPLIANT- TIRE SHINE/DRESSING

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.4 04/23/2025 600000000130 Date of first issue: 05/23/2016

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard

Revision Date : 04/23/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN