



# Wicked Clean Industrial Degreaser

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 3/17/2025 Version: 1.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Wicked Clean Industrial Degreaser  
Product code : WC-104, WC105-5, WC155-5

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Degreaser  
Restrictions on use : None known

#### 1.4. Supplier's details

DSI Automotive Products  
1271 Fayland Dr.  
Fargo, ND 58102  
701-282-8451

#### 1.5. Emergency phone number

Emergency number : (Chemical Spills, Leaks, Fire, Exposure or Accident only)  
CHEMTREC 1-800-535-5053

### SECTION 2 Hazard Identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Corrosive to metals, Category 1	H290	May be corrosive to metals.
Skin corrosion/irritation, Category 1	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs (respiratory system) through prolonged or repeated exposure.

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger  
Hazard statements (GHS US) : H290 - May be corrosive to metals  
H314 - Causes severe skin burns and eye damage  
H373 - May cause damage to organs (respiratory system) through prolonged or repeated exposure

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS US) : P234 - Keep only in original packaging.  
P260 - Do not breathe dusts or mists.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear protective gloves, eye protection, face protection, protective clothing.  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a POISON CENTER or doctor/physician.  
P314 - Get medical advice or attention if you feel unwell.  
P363 - Take off immediately all contaminated clothing and wash it before reuse.  
P390 - Absorb spillage to prevent material-damage.  
P405 - Store locked up.  
P501 - Dispose of contents to an approved waste disposal plant.

## 2.3. Hazards associated with known or reasonably anticipated uses

None known

## 2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

## 2.5. Unknown acute toxicity

No additional information available

# SECTION 3 Composition/information on ingredients

## 3.1. Substances

Not applicable

## 3.2. Mixtures

Name	Product identifier	%
C9-11 Ethoxylated Alcohol	CAS-No.: 68439-46-3	5-10
Sodium xylenesulfonate	CAS-No.: 1300-72-7	5 – 10
Tetrasodium EDTA	CAS-No.: 64-02-8	1-5
Sodium silicate	CAS-No.: 1344-09-8	1-5
Sodium Hydroxide	CAS-No.: 1310-73-2	1-5

Comments : \*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret  
Full text of hazard classes and H-statements : see section 16

# SECTION 4 First aid measures

## 4.1. Description of necessary first-aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician immediately.  
First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Immediately flush skin with plenty of water for at least 15 minutes. Get immediate medical advice/attention.

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Call a physician immediately.

## 4.2. Most important symptoms/effects, acute and delayed

Inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Skin	: May cause burns.
Eyes	: Causes serious eye damage.
Ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: None known.

## 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Get immediate medical attention.
-----------------------------------	------------------------------------

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: This product is not classified as flammable or combustible. Combustion products may include the following: carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide), nitrogen oxides (NO, NO <sub>2</sub> , etc.).
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable protective clothing. Avoid contact with eyes, skin and clothing. Always wash hands after handling the product. Do not touch or walk on the spilled product. Evacuate area.
------------------	--

#### For non-emergency personnel

Emergency procedures	: Do not breathe spray, vapors. Avoid contact with skin and eyes.
----------------------	---

#### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

Environmental precautions	: Avoid release to the environment.
---------------------------	-------------------------------------

### 6.2. Methods and materials for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Neutralize spill carefully with any weak acid and flush remainder with plenty of water. Take up liquid spill into absorbent material. Pick up and dispose of with suitable equipment.
Other information	: Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Do not get in eyes, on skin, or on clothing. Wear protective clothing, protective gloves, eye protection, face protection. Wash thoroughly after handling. Do not breathe mist, vapors. Wash hands with water and soap. Ensure adequate ventilation.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store locked up.
Incompatible materials	: Keep away from strong acids and strong oxidizers. May be corrosive to metals.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

#### Sodium Hydroxide (1310-73-2)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Sodium hydroxide
ACGIH OEL Ceiling	2 mg/m <sup>3</sup>
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2024

##### USA - OSHA - Occupational Exposure Limits

Local name	Sodium hydroxide
OSHA PEL (TWA)	2 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure adequate ventilation.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

#### Materials for protective clothing:

Impervious clothing

#### Hand protection:

Butyl-rubber protective gloves

#### Eye protection:

Goggles + face shield

#### Skin and body protection:

Wear suitable protective clothing

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

## Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Yellow liquid.
Color	: Yellow
Odor	: lemon-like
Odor threshold	: No data available
pH	: 11.5
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °F
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.1
Solubility	: soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.
Particle characteristics	: Particle characteristics : Not applicable

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Oxidizing agent. Acids. May be corrosive to metals.

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

## 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### C9-11 Ethoxylated Alcohol (68439-46-3)

LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 1.6 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

#### Sodium Hydroxide (1310-73-2)

LD50 oral	Corrosive material. Acute toxicity (oral) Classification not possible
LD50 dermal	Corrosive material. Acute toxicity (dermal) Classification not possible.

#### Tetrasodium EDTA (64-02-8)

LD50 oral rat	1780 mg/kg
---------------	------------

#### Sodium xylenesulfonate (1300-72-7)

LD50 oral rat	1000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

#### Sodium silicate (1344-09-8)

LD50 oral rat	3400 mg/kg Source: SIDS
LD50 dermal rat	> 5000 mg/kg body weight
LC50 Inhalation - Rat	> 2.06 mg/l air

Skin corrosion/irritation : Causes severe skin burns.  
pH: 11.5

#### Sodium silicate (1344-09-8)

pH	11 – 12
----	---------

Serious eye damage/irritation : Causes serious eye damage.  
pH: 11.5

#### Sodium silicate (1344-09-8)

pH	11 – 12
----	---------

Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

#### Sodium silicate (1344-09-8)

NOAEL (animal/female, F0/P)	> 159 mg/kg body weight (rat)
-----------------------------	-------------------------------

STOT-single exposure : Not classified

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

<b>Sodium silicate (1344-09-8)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (respiratory system) through prolonged or repeated exposure.
<b>C9-11 Ethoxylated Alcohol (68439-46-3)</b>	
NOAEL (oral,rat,90 days)	≥ 500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
<b>Tetrasodium EDTA (64-02-8)</b>	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air (OECD 413 method)
NOAEL (oral,rat,90 days)	≥ 500 mg/kg body weight Animal: rat, Animal sex: male
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
<b>Power Play Industrial Degreaser</b>	
Viscosity, kinematic	No data available
Inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Skin	: May cause burns.
Eyes	: Causes serious eye damage.
Ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: None known.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

<b>C9-11 Ethoxylated Alcohol (68439-46-3)</b>	
LC50 - Fish [1]	5 – 7 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2.5 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	1.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
<b>Sodium Hydroxide (1310-73-2)</b>	
EC50 - Crustacea [1]	40.4 mg/l
<b>Tetrasodium EDTA (64-02-8)</b>	
EC50 - Crustacea [1]	140 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	> 60 mg/l Pseudokirchneriella subcapitata
LOEC (chronic)	50 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 25.7 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Sodium silicate (1344-09-8)	
LC50 - Fish [1]	1108 mg/l Danio rerio (Zebrafish)
EC50 - Crustacea [1]	1700 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	207 mg/l Desmodesmus subspicatus
EC50 72h - Algae [2]	> 345.4 mg/l Desmodesmus subspicatus

## 12.2. Persistence and degradability

Power Play Industrial Degreaser	
Persistence and degradability	No additional information available.
C9-11 Ethoxylated Alcohol (68439-46-3)	
Persistence and degradability	Readily biodegradable.
Sodium Hydroxide (1310-73-2)	
Persistence and degradability	Biodegradation is not applicable to inorganic compounds.
Tetrasodium EDTA (64-02-8)	
Persistence and degradability	Not readily biodegradable.
Sodium xylenesulfonate (1300-72-7)	
Persistence and degradability	No additional information available.
Sodium silicate (1344-09-8)	
Persistence and degradability	Rapidly degradable

## 12.3. Bioaccumulative potential

Tetrasodium EDTA (64-02-8)	
Bioaccumulative potential	Low bioaccumulation potential.

## 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

Fluorinated greenhouse gases :  
: No

## SECTION 13 Disposal considerations

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.  
Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

## SECTION 14 Transport information





In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1760	UN1760	1760	1760



# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

DOT	TDG	IMDG	IATA
<b>14.2. Proper Shipping Name</b>			
Corrosive liquids, n.o.s. (CONTAINS : Sodium Hydroxide ; Tetrasodium EDTA)	CORROSIVE LIQUID, N.O.S. (CONTAINS : Sodium Hydroxide ; Tetrasodium EDTA)	CORROSIVE LIQUID, N.O.S. (CONTAINS : Sodium Hydroxide ; Tetrasodium EDTA)	Corrosive liquid, n.o.s. (CONTAINS : Sodium Hydroxide ; Tetrasodium EDTA)
<b>14.3. Transport hazard class(es)</b>			
8	8	8	8
			
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

## 14.6. Transport in bulk

Not applicable

## 14.7. Special precautions for user

### DOT

UN-No. (DOT)	: UN1760
DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"

### TDG

UN-No. (TDG)	: UN1760
--------------	----------

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

TDG Special Provisions	: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks. 2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act".
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L
Emergency Response Guide (ERG) Number	: 154
<b>IMDG</b>	
Special provision (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: SW2
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

<b>IATA</b>	
Special provision (IATA)	: A3, A803
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 8L

## SECTION 15 Regulatory information

### 15.1. Federal regulations

#### Power Play Industrial Degreaser

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

## Sodium Hydroxide (1310-73-2)

CERCLA RQ

1000 lb

## 15.2. International regulations

### CANADA

#### C9-11 Ethoxylated Alcohol (68439-46-3)

Listed on the Canadian DSL (Domestic Substances List)

#### Sodium Hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

#### Tetrasodium EDTA (64-02-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Sodium xylenesulfonate (1300-72-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Sodium silicate (1344-09-8)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

#### C9-11 Ethoxylated Alcohol (68439-46-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Sodium Hydroxide (1310-73-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Tetrasodium EDTA (64-02-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Sodium xylenesulfonate (1300-72-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

## 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Component	State or local regulations
Sodium Hydroxide(1310-73-2)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date : 3/17/2025

Data sources : This safety data sheet was compiled with data and information from the following sources :  
ECHA, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

Full text of hazard classes and H-statements	
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.