

# TECHNICAL DATA SHEET

## TECHNICIAN'S CHOICE

### TEC99200 SILICONE LUBRICANT (AEROSOL)

---

**TEC99200 SILICONE LUBRICANT** is a blend of silicones and fast evaporating non-chlorinated solvents. **TEC99200** stops squeaking, sticking, and binding and retards corrosion. **TEC99200** finds use in the textile, automotive, automatic vending machines, heat sealing and packaging equipment.

#### OUTSTANDING FEATURES

- Non-Chlorinated
- Fast Evaporating
- Leaves No Foreign Residue
- Clear Liquid
- Excellent Spray Pattern

#### PHYSICAL PROPERTIES

- Mist – Spray Pattern
- Clear Liquid
- Solvent Odor
- Contains Hexane
- Extremely Flammable

**DIRECTIONS FOR USE:** Thoroughly clean surface to be sprayed. Spray a light film with a sweeping motion. When used on sticky surfaces, work object back and forth. **TEC99200** may affect certain surfaces. Test in an inconspicuous area before general use.

**CAUTION:** Contents under pressure, keep away from heat, sparks, open flames. Use with adequate ventilation. Avoid prolonged breathing of vapor or mist. Avoid contact with eyes or prolonged or repeated contact with skin. Do not puncture or incinerate container. Do not store in direct sunlight or temperatures exceeding 120°F.

#### **EMERGENCY FIRST AID:**

Skin Contact: Wash affected areas with soap and water.

Eye Contact: Flush eyes with water for at least fifteen (15) minutes. Get medical attention. Ingestion: Do not induce vomiting, get medical attention.

Inhalation: Provide fresh air. Give artificial respiration. If necessary, get medical attention

**DANGER – EXTREMELY FLAMMABLE**

**KEEP OUT OF REACH OF CHILDREN**

**FOR PROFESSIONAL USE ONLY**

**REFER TO MSDS BEFORE USE**

**ALWAYS WEAR RECOMMENDED SAFETY EQUIPMENT**

**USE IN WELL VENTILATED AREA**